

Worldwide Pollution Control Association

IL Regional Technical Seminar
September 13-15, 2011

W
P
C
A



Visit our website at www.wpca.info

Babcock Power Inc.



The Future Of Coal Fired SCRs In A ~~Carbon Capture World~~

2011 WPCA IL

September 13, 2011



www.babcockpower.com

Introduction – Future Coal Plants

- Integrated Gasification Combined Cycle (IGCC), oxy-fuel combustion or post-combustion fuel gas CO₂ capture
 - With exception of purification of oxy-fuel derived flue gas, all will require AQCS systems
- Competing against gas turbines firing natural gas or coal synthesis gas
 - Achieve 2 to 5 ppm outlet NO_x
- What will it take to match this level with coal fired units?



Introduction – Present State Of Art

- Low NO_x burners with Selective Catalyst Reduction (SCR)
 - 90% to 92.5% NO_x reduction in SCR
 - 0.03 lb/MBtu (22 ppmvd) to 0.04 lbs./MBtu (29 ppmvd) outlet NO_x
 - 2 ppm ammonia slip
 - Effect on downstream equipment
 - Sale of flyash
 - Assuming a lack of economical method of removal of ammonia from flyash
 - Condensable PM



Necessary Input Values Of The MEA – Process

	PM [mg/Nm³] grs/scf lb/MMBtu	NO_x as NO₂ [mg/Nm³] ppm lb/MMBtu	SO_x as SO₂ [mg/Nm³] ppm lb/MMBtu
13. BlmSchV (FRG 2004)	< 20 0.0012 0.0025	< 200 (solid fuel) 97.4 0.135	< 200 70 0.135
input values of the MEA - Process	< 15 0.00095 0.0020	< 30 (NO₂) 14.6 0.020	< 30 10.5 0.020

Daily average values for plants with thermal capacity of > 300 MW



NO_x Reduction Requirements

NO_x Reduction required to Meet 2 and 5 ppm Outlet NO_x

Coal Type		SCR NO _x Reduction Wall-Fired Boiler	SCR NO _x Reduction Tangential Fired Boiler
PRB-Lignite	Baseline NO _x , ppm	180	130
	Overall Reactor Reduction	97.22%	96.15%
	Outlet NO _x , ppm	5	5
	Overall Reactor Reduction	98.89%	98.46%
	Outlet NO _x , ppm	2	2
Low - Medium Sulfur Coal	Baseline Nox	285	215
	Overall Reactor Reduction	98.25%	97.67%
	Outlet NO _x , ppm	5	5
	Overall Reactor Reduction	99.30%	99.07%
	Outlet NO _x , ppm	2	2
High Sulfur Coal	Baseline Nox	360	285
	Overall Reactor Reduction	98.61%	98.25%
	Outlet NO _x , ppm	5	5
	Overall Reactor Reduction	99.44%	99.30%
	Outlet NO _x , ppm	2	2

Source: “Advanced SCR Design Assessments for NO_x Less than 5 ppm”, by R. Himes et. al.




The 95% SCR

- More catalyst can only do so much
 - If NO_x is not there to react, NH_3 will slip through = “distribution induced slip”
- Higher removals through better mixing
 - The more uniform the NH_3/NO_x profile, the greater the catalyst performance and the lower the distribution induced slip
 - Maximum design NH_3/NO_x standard deviation to be 2 – 3 %
 - Current BPEI test data for NH_3/NO_x standard deviation are < 2%
 - Actual test results show 94.2% removal with NH_3/NO_x standard deviation of <2% yield undetectable slip for new catalyst
(Based on catalyst design of 2 ppm slip – expected to be met)



Limitations On High NO_x Removal

- Temperature, velocity, and NH₃/NO_x distribution
 - Key limitation is NH₃/NO_x distribution
 - NO_x and ammonia become progressively more non-uniform as it passes down through catalyst layers




Source: “Enhanced Ammonia Distribution for Maximum SCR Performance”, R. Sigling et. al.



Effect Of Increasing NO_x Removal


Catalyst Volume - Distribution



Source: "Selective Decomposition of Ammonia for Coal-fired Power Plant Selective Catalytic Reduction Application" by J. Bertole et. al.




Impact Of RMS On NH₃ Slip



Source: FERCO Engineering



Mixing System Results



Effect Of Increasing NO_x Removal

- Rapid increase in catalyst volume
- Increase in cross-sectional area
 - Increased difficulty in achieving uniform distribution
- Increase the number of catalyst layers
 - More expensive catalyst management
 - Possible requirement to replace more than one layer at each outage
 - Increased pressure drop



NO_x Reduction With Two Reactors

90% NO_x Removal In First SCR Reactor

Coal Type		SCR NO _x Reduction Wall-Fired Boiler	SCR NO _x Reduction Tangential Fired Boiler
PRB-Lignite	Baseline Inlet NO _x , ppm	180	130
	NO _x at Outlet of First Reactor, ppm	18	13
	Second Reactor Reduction	72.22%	61.54%
	Outlet NO _x , ppm	5	5
	Second Reactor Reduction	88.89%	84.62%
	Outlet NO _x , ppm	2	2
Low - Medium Sulfur Coal	Baseline Inlet NO _x , ppm	285	215
	NO _x at Outlet of First Reactor, ppm	28.5	21.5
	Second Reactor Reduction	82.46%	76.74%
	Outlet NO _x	5	5
	Second Reactor Reduction	92.98%	90.70%
	Outlet Nox	2	2
High Sulfur Coal	Baseline Inlet NO _x , ppm	360	285
	NO _x at Outlet of First Reactor, ppm	36	28.5
	Second Reactor Reduction	86.11%	82.46%
	Outlet NO _x	5	5
	Second Reactor Reduction	94.44%	92.98%
	Outlet NO _x	2	2



Multi-Stage Mixing

Two Reactors In Series – Method A

- First reactor has low outlet ammonia slip
- Second reactor is preceded by second ammonia injection
- Advantages
 - Additional injection grid allows for more ‘tuning’ of second reactor
 - Conventional (but more challenging) ammonia control for both reactors
 - Some adjustment can be made on NO_x removal split between the two reactors
- Disadvantages
 - More expensive and complicated ammonia and control systems
 - Longer mixing length required for entrance to second reactor
 - Probably not possible to construct as a retrofit
 - Additional pressure drop from additional mixing and ductwork



Multi-Stage Mixing

Two Reactors In Series – Method B

- First reactor has high outlet ammonia slip
- Second reactor is preceded only by flue gas mixing
- Advantages
 - Less catalyst in first reactor
 - Less expensive / complicated ammonia system
 - Single conventional ammonia control system
- Disadvantages
 - No ammonia distribution tuning possible for second reactor
 - More challenging flue mixing required for second reactor
 - Probably not possible to construct as a retrofit
 - Additional pressure drop from additional mixing and ductwork



Advanced Catalyst Design

Ammonia Slip Destructive Catalyst

- NO_x catalyst followed by separate ammonia destructive catalyst
 - Minimize NO_x catalyst volume while maintaining low ammonia slip
 - Requires selective catalyst that minimizes SO_2 conversion
 - Requires selective catalyst that minimizes ammonia conversion back to NO_x
 - May require two catalyst management plans



Advanced Catalyst Design

Selective Destructive Of Ammonia (Cormetech)

- NO_x catalyst that selectively reduces areas of high ammonia to smooth out NH_3/NO_x



- Special first catalyst layer
- Minimizes catalyst volume
- May require two catalyst management plans




Increase SCR Performance Through Reliability Improvements Operational Experience

- Increase reagent injection redundancy by tying Unit 1 & Unit 2 NH₃ injection systems together
- Aggressive equipment maintenance programs
- Continuous system condition monitoring
- On-line catalyst vacuuming and SAH water wash



Mixing System Improvements Operational Experience

- In-house verification of ammonia injection as needed based upon changes in:
 - Reactor de-NO_x performance
 - Fuel quality
 - Ammonia-in-ash
 - SAH ΔP



Low Temperature SCR Operation

Operational Experience

- Real-time NH_3 MIT (Minimum Injection Temperature) calculated from measured flue-gas parameters using ABS dewpoint curves
- Increased SCR performance at low-load operation
- Eliminates catalyst recovery periods
- Reduces Secondary Air Heater (SAH) deposition



Optimal Control Strategy

Operational Experience

- Real-time ammonia injection flow control based upon:
 - SCR outlet NO_x vs. NO_x outlet setpoint
 - SCR outlet NH_3 slip
- Real-time MIT (Minimum Injection Temperature) Permissives and trips on each reactor
- Real-time catalyst ΔT monitoring
- Real-time ABS monitoring
- Parallel reactors are controlled independently




Improved Catalyst Inlet Ammonia- NO_x Ratio

- Increase mixing during initial design at cost of pressure loss
- Current designs have obtained less than 1 % RMS during testing
- Use mixing system design with active controls
- Designs must be reliable and able to alert operators



Design Of <2% RMS Mixing System

- Babcock Power studied the effect of individual mixings during model study
- Model study results verified with multiple field tests
- Mathematical optimization performed in model and field scale confirming design



System Requirement For Enhanced Control

- Mixing system design is predictable and repeatable
- Model study accurately provides full scale injector influences
- One to one correspondence of NO_x measurement to injection point
- Furnace NO_x SCR inlet influence controlled




Valve Influence Test And Optimization Test


- Constant ammonia flow
- Test each valve individually
- Plot results for each valve
- Create influence coefficient matrix
- Computer optimization program
 - Linear equations
 - Ammonia flow constraints
- Review and adjust valves




Injector Influence: Coal-Fired 400 MW SCR Reactor *




BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 5 Test Date: 7/17/03 Test Start Time: 2052 Test End Time: 2106
 Test Description: Full Load Valve Influence Test - Valve 5
 Avg Outlet NOx ppm: 282 % Removal: 30 Std Deviation: 93.5




BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 3 Test Date: 7/17/03 Test Start Time: 2233 Test End Time: 2247
 Test Description: Full Load Valve Influence Test - Valve 3
 Avg Outlet NOx ppm: 284 % Removal: 29 Std Deviation: 93.2




BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 1 Test Date: 7/17/03 Test Start Time: 2144 Test End Time: 2200
 Test Description: Full Load - Valve Influence Test Valve #1
 Avg Outlet NOx ppm: 285 % Removal: 29 Std Deviation: 115.4



BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 6 Test Date: 7/17/03 Test Start Time: 2117 Test End Time: 2131
 Test Description: Full Load Valve Influence Test - Valve 6
 Avg Outlet NOx ppm: 287 % Removal: 28 Std Deviation: 113.2



BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 4 Test Date: 7/17/03 Test Start Time: 2255 Test End Time: 2309
 Test Description: Full Load Valve Influence Test - Valve 4
 Avg Outlet NOx ppm: 279 % Removal: 30 Std Deviation: 49



BBP Contract #: 100109 Project Name: AEP UH: Big Sandy 2 Reactor: R1
 Test: Big Sandy R1 071703 V2 Valve 2 Test Date: 7/17/03 Test Start Time: 2211 Test End Time: 2255
 Test Description: Full Load Valve Influence Test - Valve 2
 Avg Outlet NOx ppm: 276 % Removal: 31 Std Deviation: 107.2

*** Benes & Erickson, Electric Power 2005**



Automatic Control – Example

- 180 MW gas fired single unit
- Poor ammonia flow control at non-design low injection rates
- Solution enhanced ammonia control
 - Limited number of NH₃ injectors
 - Clearly defined influence fields
 - Modified with additional outlet NO_x meter for two feedback loops
- Installed in summer 2005
- Extended time between injection point ‘tune ups’



Automatic Control – Example



Summary

Meeting 2 – 5 ppm Outlet NO_x

- Outlet Values can be met with multiple reactors but at substantial cost
- Alternate catalyst technologies can meet this level of performance but are under development
- Outlet NO_x levels of 2 – 5 ppm are achievable with additional mixing and controls



**Babcock Power would like to thank
Wayne Whitaker, Duke Energy, for his
contribution to and support of this work**

Thank You

DISCLAIMER

The contents of this paper contain the views and analyses of the individual authors only. The paper is offered to chronicle developments and/or events in the field, but is not intended and is not suitable to be used for other purposes, including as a professional design or engineering document. Babcock Power Inc., its subsidiaries and employees, make no representations or warranties as to the accuracy or completeness of the contents of this paper, and disclaim any liability for the use of or reliance upon all or any portion of the contents of this paper by any person or entity.

